

CRXG 2





## **GENERAL FEATURES**


| 200 Lt. Refrigerated upright (GLASS DOOR)             | • |
|---|---|
| S/S external cabinet, thermoformed internally         | • |
| Roll-bond evaporator system with fan assisted cooling | • |
| Automatic compressor cycle defrost                    | • |
| Foaming Agent Cyclopentane (50mm per side)            | • |
| Digital Thermostat and internal LED light             | • |
| High temperature alarm                                | • |
| Removable Gasket                                      | • |
| Reversible door                                       | • |
| Lock and main switch fitted as standard               | • |
| Adjustable shelves: 2 Pcs + 1 Pcs Bottom              | • |
| N.2 Adjustable feet + N.2 Rollers at the back         | • |
| Stainless steel external handle                       | • |
| Energy efficiency class: A                            | • |
|   |   |

## **PRODUCT DIMENSIONS**

## **TECHNICAL SPECIFICATIONS** Capacity 200 L Temperature +2°C ~ +8°C Consumption 1.036 kWh/24h Rated Power 60 W Noise level 40 dB(A) Net Weight 46.2 Kg Gross Weight 50.5 Kg External Dimensions (WxDxH mm) 598x679x838 Internal Dimensions (WxDxH mm) 477x443x652 Packaging dimensions (WxDxH mm) 650x680x880 Loading quantities 20'/40'/40'HQ 48/108/162

(( C

RoHS



## CERTIFICATION

