

SL 260




FROZEN DICE

Self-contained ice maker - Sprayer system
Daily production up to 104 kg

• Position n°



• Available dice size



• Application fields

Hotel	●●●●●●●●●●	Fish market	●●●●●●●●●●
Restaurant	●●●●●●●●●●	Supermarket	●●●●●●●●●●
Fast food	●●●●●●●●●●	SPA	●●●●●●●●●●
Bar	●●●●●●●●●●	Medical	●●●●●●●●●●
Disco	●●●●●●●●●●	Industry	●●●●●●●●●●

• Features & Plus

- Full cube, compact and crystalline
- External structure AISI 304 Scotch Brite
- Side grilles for better ventilation
- Removable side panels
- Electromechanical functioning
- Air Cooling and Water Cooling systems
- Standard and special voltages
- Insulated retractable door
- ON-OFF switch
- Internal bin insulation HCFC free
- Conformity to RoHS directive
- Easy cleaning thanks to rounded surfaces
- Model in Tropical Class + 43 ° C
- External protective filter, removable, easy to clean
- Adjustable Stainless Steel feet

• Prod. 24h


Air temp.	Water temp.	Prod. 24h kg
10° C	10° C	104
21° C	15° C	100
32° C	21° C	85

SL 260



FROZEN DICE

Self-contained ice maker - Sprayer system
Daily production up to 104 kg



• Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water inlet:
126 mm - 180 mm - 3/4"
- ② Water outlet:
61 mm - 246 mm - 24 mm
- ③ Electrical connection:
126 mm - 280 mm

• Working conditions

- Location: Indoor

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

• Technical information

Production in 24h	100 kg
Store capacity, up to	60 kg
Cooling system	A - W
Kind of cube	14-17-32-41 g
Refrigerant	R404A - R452A
Standard voltage	220-240 V ~ 50 Hz
Electrical consumption	850 W
Fuse	10 A
Water consumption	A: 2,5 l/kg W: 14,2 l/kg
Sizes (L-P-H mm)	735 - 603 - 1007
Sizes with pack (L-P-H mm)	780 - 640 - 1185
Net weight	74 kg
Gross weight	86 kg
Finish	AISI 304 stainless steel, scotch brite

All the technical information must be considered
at the following conditions:

Sizes without feet	Standard Cube (17 g)	Ambient temperature +21° C	Water temperature +15° C	Electrical consumption at +43° C (standard voltage)