

MKF 2011 TS



Forno elettrico combinato convezione vapore

20 teglie 1/1 GN con TOUCH SCREEN

Electric combi oven 20 trays

1/1 GN with TOUCH SCREEN



Plus

Sistema carter d'aria brevettato Airflowlogic™	
Sistema vapore diretto brevettato Humilogic™	
Sistema essiccazione in camera cottura brevettato Drylogic™	
Su richiesta in fase d'ordine	Voltaggio (V) : AC 220/230 3 PH Porta apertura laterale sx *
Software per gestione dell'umidità	
Sistema comunicazione Wi-Fi	
Manopola selezione rapida touch screen	
Accensione forno programmabile	
N° 40 ricette memorizzate	
Pannello comandi in 42 lingue	
italiano, arabo, armeno, azero, bahasa (indonesia), bahasa (malesia), bosniaco, bulgaro, ceco, cinese, sud coreano, croato, danese, estone, filippino, finlandese, francese, georgiano, giapponese, greco, inglese, islandese, kazako, lituano, lettone norvegese, olandese, persiano (iran), polacco, portoghese, rumeno, russo, serbo, sloveno, spagnolo, svedese, tedesco, thailandese, turco, ucraino, ungherese, vietnamita	
Sistema per HACCP	
Cerniere porta regolabili	

* aggiunta 300 € su prezzo di listino

Dotazione di serie

Imballo cartone+pallet (LxPxH mm)	1146 x 1260 x 2090 mm
Presenza USB	
Sonda al cuore multipunto cod. MKSCMU/B	
Supporto sonda al cuore cod. MKSSC/A	
Lavaggio automatico integrato	
Cerniera con bloccoporta per aperture regolate a 60°, 90°, 120°, 180°	
Carrello estraibile con impugnatura e ruote dotate di freno cod. EKCR 20 TC	

Dimensioni

Dimensioni (LxPxH mm)	930 x 1035 x 1900
Peso (kg)	247,2
Passo guide (mm)	66

Caratteristiche elettriche

Potenza elettrica (kW)	31
Frequenza (Hz)	50/60
Voltaggio (V)	AC 380/400 3N
N° motori	4 bidirezionali
Generatore di vapore (kW)	/
Protezione acqua	IPX5

Caratteristiche funzionali

Alimentazione	Elettrico
Capacità	N° 20 teglie/griglie 1/1 GN
Cottura	Semistatica + ventilata
Vapore	Diretta con regolazione automatica attraverso selettore touch screen (10 steps)
Camera di cottura	Acciaio AISI 304
Temperatura	30 - 270 °C
Controllo temperatura	2 Sonde digitali
Pannello comandi	Touch screen
N° programmi	500
Fasi programmabili	10
Temperatura preimpostata	180 °C
Preriscaldamento	Disponibile
Porta	Apertura laterale dx Ventilata Vetro ispezionabile
Piedini	Regolabili

Accessori

Cappa aspirazione	MKKC 1620
Carrello	EKCR 20 TC
Altri accessori	Consultabili nella sezione dedicata



Plus

Patented fan guard system Airflowlogic™	
Patented system for direct steam Humilogic™	
Patented system for cooking chamber drying Drylogic™	
Available on request at the order	Voltage (V) : AC 220/230 3 PH Left side opening door *
Humidity management software	
Wi-Fi communication system	
Knob for quick selection of the touch screen	
Programmable oven start	
N° 40 recipes stored	
Control panel in 42 languages:	
Arabic, Armenian, Azerbaijani, Bahasa (Indonesia), Bahasa (Malaysia), Bosnian, Bulgarian, Chinese, Croatian, Czech, Danish, Dutch, English, Estonian, Finnish, French, Georgian, German, Greek, Hungarian, Icelandic, Italian, Japanese, Kazakh, Latvian, Lithuanian, Norwegian, Persian (Iran), Philippine, Polish, Portuguese, Romanian, Russian, Serbian, Slovenian, South Korean, Spanish, Swedish, Thai, Turkish, Ukrainian, Vietnamese	
HACCP system	
Adjustable door hinges	

* addition of 300 € on the price list

Equipment

Cardboard box dimensions with pallet (WxDxH mm)	1146 x 1260 x 2090 mm
USB port	
Multipoint core probe cod. MKSCMU/B	
Support for core probe cod. MKSSC/A	
Automatic washing system integrated	
Hinge with door locking for openings adjusted at 60°, 90°, 120°, 180°	
Trolley with removable handle and braked wheels cod. EKCR 20 TC	

Dimensional features

Dimensions (WxDxH mm)	930 x 1035 x 1900
Weight (kg)	247,2
Distance between rack rails (mm)	66

Electrical features

Power supply (kW)	31
Frequency (Hz)	50/60
Voltage (V)	AC 380/400 3N
N° motors	4 bidirectionals
Boiler (kW)	/
Protection against water	IPX5

Functional features

Power	Electricity
Capacity	N° 20 trays/grids 1/1 GN
Type of cooking	Semistatic + ventilated
Steam	Direct steam controlled by touch screen (10 levels)
Cooking chamber	AISI 304 stainless steel
Temperature	30 - 270 °C
Temperature control	2 Digital probe thermometers
Control panel	Touch screen
N° programs	500
Programmable cooking steps	10
Pre-heating temperature	180 °C
Pre-heating function	Programmable
Door	Right side opening Ventilated Inspectionable glass
Feet	Adjustable

Optionals

Condensation hood	MKKC 1620
Trolley	EKCR 20 TC
Other accessories	Available in the dedicated section