

Information sheet (Lot.10)

This information includes the results of calculation of the seasonal energy consumption and efficiency for air conditioner in regards to ErP pursuant to the Commission Regulation(EU) No.206/2012 and No.626/2011.

Information to identify the mode(s) to which the information relates to:

AIR CONDITIONER
 TYPE : MULTI SPLIT
 WALL MOUNTED
 Indoor unit(s) : ASHG07KMCE x 1 + ASHG09KMCE x 2
 Outdoor unit : AOHG24KBTA3
 BRAND : GENERAL

N/A = Not Applicable

Function			
Cooling	Yes	Average	Yes
Heating	Yes	Warmer	No
		Colder	No

Design load				Seasonal efficiency			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Cooling	Pdesignc	6.8	kW	Cooling	SEER	8.50	-
Heating/Average	Pdesignh	6.0	kW	Heating/Average	SCOP/A	4.60	-
Heating/Warmer	Pdesignh	N/A	kW	Heating/Warmer	SCOP/W	N/A	-
Heating/Colder	Pdesignh	N/A	kW	Heating/Colder	SCOP/C	N/A	-

Cooling							
Declared capacity for cooling, at indoor temperature 27 (19) °C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27 (19) °C and outdoor temperature Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = 35°C	Pdc	6.80	kW	Tj = 35°C	EER d	3.90	-
Tj = 30°C	Pdc	5.01	kW	Tj = 30°C	EER d	6.05	-
Tj = 25°C	Pdc	3.22	kW	Tj = 25°C	EER d	10.51	-
Tj = 20°C	Pdc	2.84	kW	Tj = 20°C	EER d	16.79	-

Heating/Average							
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Average season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = -7°C	Pdh	5.31	kW	Tj = -7°C	COPd	2.80	-
Tj = 2°C	Pdh	3.23	kW	Tj = 2°C	COPd	4.67	-
Tj = 7°C	Pdh	3.06	kW	Tj = 7°C	COPd	6.30	-
Tj = 12°C	Pdh	2.84	kW	Tj = 12°C	COPd	8.05	-
Tj = bivalent temperature	Pdh	5.31	kW	Tj = bivalent temperature	COPd	2.80	-
Tj = operating limit	Pdh	4.99	kW	Tj = operating limit	COPd	2.55	-

Heating/Warmer							
Declared capacity for heating/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Warmer season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = 2°C	Pdh	N/A	kW	Tj = 2°C	COPd	N/A	-
Tj = 7°C	Pdh	N/A	kW	Tj = 7°C	COPd	N/A	-
Tj = 12°C	Pdh	N/A	kW	Tj = 12°C	COPd	N/A	-
Tj = bivalent temperature	Pdh	N/A	kW	Tj = bivalent temperature	COPd	N/A	-
Tj = operating limit	Pdh	N/A	kW	Tj = operating limit	COPd	N/A	-

Heating/Colder							
Declared capacity for heating/Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Colder season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Tj = -7°C	Pdh	N/A	kW	Tj = -7°C	COPd	N/A	-
Tj = 2°C	Pdh	N/A	kW	Tj = 2°C	COPd	N/A	-
Tj = 7°C	Pdh	N/A	kW	Tj = 7°C	COP d	N/A	-
Tj = 12°C	Pdh	N/A	kW	Tj = 12°C	COP d	N/A	-
Tj = bivalent temperature	Pdh	N/A	kW	Tj = bivalent temperature	COP d	N/A	-
Tj = operating limit	Pdh	N/A	kW	Tj = operating limit	COP d	N/A	-
Tj=-15°C	Pdh	N/A	kW	Tj = -15°C	COP d	N/A	-

Bivalent temperature				Operating limit temperature			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heating/Average	T _{biv}	-7	°C	Heating/Average	T _{ol}	-15	°C
Heating/Warmer	T _{biv}	N/A	°C	Heating/Warmer	T _{ol}	N/A	°C
Heating/Colder	T _{biv}	N/A	°C	Heating/Colder	T _{ol}	N/A	°C

Cycling interval capacity				Cycling interval efficiency			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
For cooling	P _{cycc}	N/A	kW	For cooling	EER _{cycc}	N/A	-
For heating	P _{cycc}	N/A	kW	For heating	COP _{cycc}	N/A	-
Degradation coefficient cooling	C _{dc}	0.25	-	Degradation coefficient heating	C _{dh}	0.25	-

Electric power input in power modes other than 'active mode'				Annual electricity consumption			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Off mode (Cooling/Heating)	P _{OFF}	3.0/3.0	W	Cooling	Q _{CE}	280	kWh/a
Standby mode (Cooling/Heating)	P _{SB}	3.0/3.0	W	Heating/Average	Q _{HE}	1826	kWh/a
Thermostat-off mode (Cooling/Heating)	P _{TO}	7.0/15.0	W	Heating/Warmer	Q _{HE}	N/A	kWh/a
Crankcase heater mode (Cooling/Heating)	P _{CK}	0.0/0.0	W	Heating/Colder	Q _{HE}	N/A	kWh/a

Capacity control			Other items			
Item	Y/N		Item	Symbol	Value	Unit
Fixed	No		Sound power level (Indoor/Outdoor)	L _{WA}	55.0/61.0	dB(A)
Staged	No		Global warming potential	GWP	675	kgCO ₂ eq.
Variable	Yes		Rated air flow (Indoor/Outdoor)	-	700/2270	m ³ /h

Contact details for obtaining more information	FUJITSU GENERAL LIMITED 3-3-17, Suenaga, Takatsu-ku, Kawasaki, 213-8502, Japan
--	---

V20121214

Information of indoor unit combination

N/A = Not Applicable

Combination of Indoor unit *1			Cooling				Heating/Average				Heating/Warmer				Heating/Colder			
room1	room2	room3	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class
			Pdesigngc kW	SEER	Q _{CE} kWh/a	-	Pdesigngh kW	SCOP/A	Q _{HE} kWh/a	-	Pdesigngh kW	SCOP/W	Q _{HE} kWh/a	-	Pdesigngh kW	SCOP/C	Q _{HE} kWh/a	-
07	07	-	4.0	8.3	169	A++	4.0	4.2	1333	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	-	4.5	8.2	192	A++	4.0	4.2	1333	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	-	5.5	8.0	241	A++	5.0	4.0	1750	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	14	-	6.0	7.6	276	A++	5.4	4.0	1890	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	18	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	-	5.0	8.1	216	A++	4.5	4.1	1537	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	-	6.0	7.6	276	A++	5.4	4.0	1890	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	14	-	6.5	7.2	316	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	18	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	12	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	14	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	18	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	14	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	18	-	6.8	6.9	344	A++	5.8	4.0	2028	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	07	6.0	8.6	244	A+++	5.4	4.7	1609	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	09	6.5	8.5	268	A+++	5.8	4.6	1765	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	18	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	09	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	18	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	14	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	09	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	18	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	14	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	12	12	6.8	8.5	280	A+++	6.0	4.6	1826	A++	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

*1
 07 = 7000Btu/h class = 2.0kW class
 09 = 9000Btu/h class = 2.5kW class
 12 = 12000Btu/h class = 3.5kW class
 14 = 14000Btu/h class = 4.0kW class
 18 = 18000Btu/h class = 5.0kW class

Indoor unit combination (except all indoor unit WALL MOUNTED KG/KM/KE type)

N/A = Not Applicable

Combination of Indoor unit *1			Cooling				Heating/Average				Heating/Warmer				Heating/Colder			
room1	room2	room3	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class	Design load	Seasonal efficiency	Annual electricity consumption	Energy efficiency class
			Pdesigngc	SEER	QCE	-	Pdesigngh	SCOP/A	QHE	-	Pdesigngh	SCOP/W	QHE	-	Pdesigngh	SCOP/C	QHE	-
			kW	-	kWh/a		kW	-	kWh/a		kW	-	kWh/a		kW	-	kWh/a	
05	09	-	4.0	6.7	209	A++	4.0	4.0	1400	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	12	-	5.0	6.5	269	A++	4.5	3.9	1615	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	14	-	5.5	6.4	301	A++	5.0	3.8	1842	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	18	-	6.5	5.5	414	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	-	4.0	6.7	209	A++	4.0	4.0	1400	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	-	4.5	6.6	239	A++	4.0	4.0	1400	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	-	5.5	6.4	301	A++	5.0	3.8	1842	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	14	-	6.0	6.0	350	A+	5.4	3.8	1989	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	18	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	-	5.0	6.5	269	A++	4.5	3.9	1615	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	-	6.0	6.0	350	A+	5.4	3.8	1989	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	14	-	6.5	5.5	414	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	18	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	12	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	14	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	18	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	14	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
14	18	-	6.8	5.2	458	A	5.8	3.8	2137	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	05	4.5	6.6	239	A++	4.0	4.2	1333	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	07	5.0	6.5	269	A++	4.5	4.1	1537	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	09	5.5	6.4	301	A++	5.0	4.1	1707	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	12	6.5	6.2	367	A++	5.8	3.9	2082	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	14	6.8	6.2	387	A++	5.9	3.9	2127	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	05	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	07	5.5	6.4	301	A++	5.0	4.1	1707	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	09	6.0	6.3	333	A++	5.4	4.0	1890	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	12	6.8	6.2	387	A++	6.0	3.9	2182	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	07	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	09	09	6.5	6.2	367	A++	5.8	3.9	2082	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	09	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	09	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	09	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	12	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	12	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	12	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
05	14	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	07	6.0	6.3	333	A++	5.4	4.0	1890	A+	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	09	6.5	6.2	367	A++	5.8	3.9	2082	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	07	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	09	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	09	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	12	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
07	14	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	09	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	09	18	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
09	12	14	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
12	12	12	6.8	6.2	384	A++	6.0	3.9	2154	A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

*1
 05 = 5000Btu/h class = 1.5kW class
 07 = 7000Btu/h class = 2.0kW class
 09 = 9000Btu/h class = 2.5kW class
 12 = 12000Btu/h class = 3.5kW class
 14 = 14000Btu/h class = 4.0kW class
 18 = 18000Btu/h class = 5.0kW class

Information of unit specification

Model Type	Model No.	Capacity Class	Dimension [H x W x D]	Sound power level(Cooling)	Sound power level(Heating)
		kW	mm	dB(A)	dB(A)
OUTDOOR	AOHG24KBT3	-	716 x 820 x 315	61	67
WALL MOUNTED	ASHH05KNCA	1.5	270 x 784 x 222	50	50
	ASHH07KNCA	2.0		51	51
	ASHH09KNCA	2.5		56	56
	ASHH12KNCA	3.5		57	57
	ASHG07KGTB	2.0		270 x 834 x 215	54
	ASHG07KGTE				
	ASHG07KGTG				
	ASHG07KGTG				
	ASHG09KGTB	2.5	55		57
	ASHG09KGTE				
	ASHG09KGTG				
	ASHG09KGTG				
	ASHG12KGTB	3.5	56		58
	ASHG12KGTE				
	ASHG12KGTG				
	ASHG12KGTG				
	ASHG14KGTB	4.0	57	59	
	ASHG14KGTE				
	ASHG14KGTG				
	ASHG14KGTG				
	ASHG07KETA	2.0	295 x 950 x 230	54	56
	ASHG07KETE				
	ASHG07KETF				
	ASHG07KETF				
	ASHG09KETA	2.5		55	57
	ASHG09KETE				
	ASHG09KETF				
	ASHG09KETF				
	ASHG12KETA	3.5		55	58
	ASHG12KETE				
	ASHG12KETF				
	ASHG12KETF				
ASHG14KETA	4.0	57	59		
ASHG14KETE					
ASHG14KETF					
ASHG14KETF					
ASHG07KETA-B	2.0	295 x 950 x 230	54	56	
ASHG07KETE-B					
ASHG07KETF-B					
ASHG07KETF-B					
ASHG09KETA-B	2.5		55	57	
ASHG09KETE-B					
ASHG09KETF-B					
ASHG09KETF-B					
ASHG12KETA-B	3.5		55	58	
ASHG12KETE-B					
ASHG12KETF-B					
ASHG12KETF-B					
ASHG14KETA-B	4.0	57	59		
ASHG14KETE-B					
ASHG14KETF-B					
ASHG14KETF-B					
ASHG07KMCC	2.0	270 x 834 x 215	54	56	
ASHG07KMCE					
ASHG07KMCF					
ASHG07KMCF					
ASHH07KMCG	2.5		55	57	
ASHG09KMCC					
ASHG09KMCE					
ASHG09KMCF					
ASHH09KMCG	3.5		55	58	
ASHG12KMCC					
ASHG12KMCE					
ASHG12KMCF					
ASHH12KMCG	4.0	57	59		
ASHG14KMCC					
ASHG14KMCE					
ASHG14KMCF					
ASHH14KMCG	2.0	270 x 834 x 215	54	56	
ASHG07KMTB					
ASHG09KMTB					
ASHG09KMTB					
ASHG12KMTB	2.5		55	57	
ASHG12KMTB					
ASHG12KMTB					
ASHG12KMTB					
ASHG14KMTB	3.5		55	58	
ASHG14KMTB					
ASHG14KMTB					
ASHG14KMTB					
ASHG18KMTB	4.0	57	59		
ASHG18KMTB					
ASHG18KMTB					
ASHG18KMTB					
ASHG18KMTB	5.0	280 x 980 x 240	60	61	
ASHG18KMTB					
ASHG18KMTB					
ASHG18KMTB					
CASSETTE	AUXG07KVLA	2.0	245 x 570 x 570 (Panel: 49 x 620 x 620)	46	47
	AUXG09KVLA	2.5		46	47
	AUXG12KVLA	3.5		49	49
	AUXG14KVLA	4.0		50	55
	AUXG18KVLA	5.0		50	55
	AUXG18KVLA	5.0		55	55
DUCT	ARXG07KSLAP	2.0	198 x 700 x 450	52	53
	ARXG09KSLAP	2.5		54	56
	ARXG12KSLAP	3.5		55	57
	ARXG14KSLAP	4.0		60	62
	ARXG18KSLAP	5.0	198 x 900 x 450	58	59
	ARXG07KLLAP	2.0	198 x 700 x 620	57	57
	ARXG09KLLAP	2.5		57	57
	ARXG12KLLAP	3.5		58	58
	ARXG14KLLAP	4.0		60	60
	ARXG18KLLAP	5.0	198 x 900 x 620	58	58
	ARXH12KMTAP	3.5	240 x 700 x 700	58	58
	ARXH14KMTAP	4.0		59	59
	ARXH18KMTAP	5.0		60	60
	ARXH18KMTAP	5.0		60	60
FLOOR	AGHG09KVCA	2.5	600 x 740 x 200	52	52
	AGHG12KVCA	3.5		55	55
	AGHG14KVCA	4.0		56	56
CEILING	ABHG18KRTA	5.0	235 x 1080 x 705	53	53